

# Precise Time & Frequency Equipment (PTFE)

Both the Caesium and Rubidium-based PTFE maintain precise time in the temporary absence of GPS satellite received time by using the US Naval Observatory-maintained coordinated Universal Time (UTC), obtained using the NAVSTAR GPS. Both are highly reliable due to self-arbitration and redundancy.

## Caesium-based PTFE Key Features



- Will maintain precise time to an accuracy of less than  $50\mu\text{sec}$  after 90 days without GPS
- Equipped with an integral 4th generation GPS receiver module to discipline a secondary Rubidium
- Caesium tube primary oscillator; Rubidium tube secondary oscillator
- Highly stable phase-lock-loop control circuit for the secondary rubidium source
- Automatic and instantaneous switching to internal source in the case of GPS signal loss or degradation
- Supports the NATO PTTI interface in accordance with STANAG 4430

## Rubidium-based PTFE Key Features



- Will maintain precise time to an accuracy of less than  $250\mu\text{sec}$  after 45 days without GPS
- Dual-redundant internal Rubidium frequency source
- Highly stable phase-lock-loop control circuit for each RB oscillator
- GPS interface in accordance with ICD-GPS-060
- Supports the NATO PTTI interface in accordance with STANAG 4430
- Currently in service with the Royal Navy as Outfit FSF, fitted to some twenty-five operational ships including Type 45 destroyers
- Currently being fitted to Type 26 and Type 31



# Technical Specifications

## Caesium-based PTFE

Frequency Accuracy	$3 \times 10^{-12}$
Short-term Frequency Stability	better than $5 \times 10^{-12}$ per day
Long-term Frequency Stability	better than $8 \times 10^{-14}$
Ageing	-
Time Accuracy (GPS accessible)	within 100ns
Time Accuracy (GPS lost)	less than $50\mu\text{s}$ after 90 days
Electrical Power Source	115V AC 60Hz / 240V AC 50Hz
Electrical Consumption	250W
Back-up Batteries	optional
Physical Characteristics	<ul style="list-style-type: none"><li>• Weight: 23kg</li><li>• Height:(5U) 222mm</li><li>• Width: (19") 482mm</li><li>• Depth: 460mm</li></ul>

## Rubidium-based PTFE

Frequency Accuracy	$5 \times 10^{-11}$
Short-term Frequency Stability	better than $2.5 \times 10^{-12}$ per day
Long-term Frequency Stability	-
Ageing	$5 \times 10^{-11}$ /month
Time Accuracy (GPS accessible)	within 100ns
Time Accuracy (GPS lost)	less than $250\mu\text{s}$ after 45 days
Electrical Power Source	115V AC 60Hz / 240V AC 50Hz
Electrical Consumption	250W
Back-up Batteries	optional
Physical Characteristics	<ul style="list-style-type: none"><li>• Weight: 50kg**</li><li>• Height:(8U) 355mm**</li><li>• Width: (19") 482mm</li><li>• Depth: 460mm</li></ul>

\*\* Including integral battery modules

## Options

- Custom interface and output signal requirements implemented (frequency outputs, time messages, fibre optic interfaces) via Interface Modules, as required, including customised distribution
- Alternative levels of redundancy available with marginal decrease in reliability
- Back-up battery available in separate shelf unit providing more than one hour at full load

